

LAMAR

UTILITY TRAILERS

TRAILERS THAT LAST



The logo features a red stylized wing or arrow icon to the left of the word "LAMAR" in a bold, italicized, white sans-serif font. Below "LAMAR" is the tagline "TRAILERS THAT LAST" in a smaller, white, all-caps sans-serif font.

LAMAR
TRAILERS THAT LAST

QUALITY & CUSTOMER SERVICE



3 Year Structural Warranty

Lamar's warranty covers the primary frame for 3 years

1 Year Component Warranty

Non wearing components are covered for 1 year.

Premium 3rd Party Component Warranty

Lamar uses high quality brands for parts and the warranty is covered by the parts respective manufacturer.

UTILITY TRAILER (UC)

3,000 - 7,000 LB GVWR

GVWR	3,000 - 7,000 lbs
Weight	1,000 - 1,500 lbs
Payload	2,000 - 5,500 lbs
Axles	Single or Tandem
Lengths	10' - 18'
Widths	60" - 83"
Frame	4" Channel
Floor	Treated Pine
Deck Height	20"
Loading Angle	20°



UC - 5k GVWR



UC - 7k GVWR



STANDARD FEATURES

Frame	4" Channel
Floor	Treated Pine
Tie Downs	Stake Pockets
Coupler	2" 7k Ram Cast Coupler
Ramps	4' Spring Assisted Laydown Gate (20°)
Crossmembers	24" Spacing
Jack	2k Top-wind Flip Jack
Top Rail	2" x 2" Angle
Spare Mount	Spare Mount

POPULAR UPGRADES

- 1 Electric Brakes
- 2 Spare Tire
- 3 2' Dove
- 4 3' Spring Assisted Gate
- 5 7k Drop-Leg Jack



Laydown Gate

UTILITY TRAILER (U5)

10,000 LB GVWR

GVWR	10,000 lbs
Weight	1,800 - 2,800 lbs
Payload	8,000 - 13,000 lbs
Lengths	12' - 24'
Widths	77" - 83"
Frame	5" Channel
Floor	Treated Pine
Deck Height	22"
Loading Angle	22°



U5 - Spare Mount

STANDARD FEATURES

Frame	5" Channel
Floor	Treated Pine
Tie Downs	Top Rail & Stake Pockets
Coupler	2 5/16" 12.5 Ram A-Frame Cast Coupler
Ramps	Slide In Ramps (22°)
Crossmembers	24" Spacing
Jack	7k Drop-leg Jack

POPULAR UPGRADES

- 1** Pipe Toprail
- 2** 5' Heavy Duty Gate (21°)
- 3** Adjustable Coupler
- 4** 2' Dove
- 5** Spare Tire Mount

UTILITY TRAILER (U6)

14,000 - 16,000 LB GVWR

GVWR	14,000 - 16,000 lbs
Weight	2,400 - 3,300 lbs
Payload	10,750 - 13,400 lbs
Lengths	12' - 26'
Widths	77" - 83"
Frame	5" - 6" Channel
Floor	Treated Pine
Deck Height	25"
Loading Angle	25°



U6 - Spare Mount

STANDARD FEATURES

Frame	6" Channel
Floor	Treated Pine
Tie Downs	Top Rail & Stake Pockets
Coupler	2 5/16" 21k Demco Adjustable Coupler
Ramps	Slide In Ramps (25°)
Crossmembers	16" Spacing
Jack	10k Drop-leg Jack

POPULAR UPGRADES

- 1 5' Heavy Duty Gate (24°)
- 2 24" Stand Up Ramps (25°)
- 3 2' Dove
- 4 Spare Mount
- 5 Pipe or Tube Top Rail



*U6 - Stand up ramps
2' Dove - (18°)*

STANDARD & POPULAR OPTIONS



Slide In Ramps



Laydown Gate



5' Heavy Duty Gate



2' Dove & 3' Gate



Angle Toprail



Pipe Toprail



lamartrailers.com

903-782-9333

info@lamartrailers.com

7271 FM 38 N, Sumner, Texas, 75486